



Cement Bonded Particleboard
Your Idea Your Style

Stair Case

Cement with wood Grain & Groove product



Anti-Termite



Durable against
weather



Good for
respiration



Nonflammable



Money & Time
saving

- The product made from Portland cement and wood
- Durable for Internal and External use
- Recommended coating with acrylic color paint

Finished Stair Case Cement with wood Grain & Groove product

Specification

Type	W*D*H	Weight/Piece (Kg.)	Piece/Pallet (Kg.)
Riser	18 x 120 x 1.6	4.7	75
	27 x 120 x 2.4	10.5	60
Tread	30 x 120 x 2.4	11.7	60
	27 x 120 x 2.4	10.5	60
Tread with groove	30 x 120 x 2.4	11.7	60
	120 x 120 x 2.4	46.7	40

Installation Guide

Installation over Grey concrete

- The surface must be dry, flat, level and fully cured
- Make sure water absorption of the substrate is at normal level. In case of new render or leveling, the substrate should be fully cured for 7 days or 168 hrs. per 1 cm thickness of adhesive before tiling.
- Longer & safety attached the stair with wing screw (Pilot hole done by drilling) at the edge of stair Space from the corner 25 mm.
- Hide screw head with acrylic filler

Installation over Grey concrete

Add Steel or steel frame along the center under stair case

- Steel thickness 23 - 32 mm.
- Frame place every 400*400 mm.
- Finished coating steel surface before attach the stair
- Attached the stair with wing screw (Pilot hole done by drilling) at the edge of stair Space from the corner 25 mm.
- Hide screw head with acrylic filler

Coating with Fiber Cement Color

- The surface must be dry, flat, level and fully cured
- Varnish with Primer paint 1 layer
- Paint with 100% Transparent acrylics for 2-3 layers to get timber-like surface by brush

Cement wood stair case V - Groove Straight grain

- Anti Slip with V-Groove straight grain
- Time saving (without nosing process)
- Easy to install like wood



Landing with groove

- More Spaces of stair landing (1.44 Sq.m./Piece)
- Quick installation & seamless
- Anti Slip with V-groove grain



Panel World Co.,Ltd.
83/1 moo11, Sethakij 1 Rd., Klongmadue,
Krathumban, Samutsakorn 74110 Thailand.
Tel. : (+66) 34 473 067-70 Fax : (+66) 34 473 063